



# **Comply With Odor Regulations & Protect Your Plants**

Controlling odor in and around your facility is a constant challenge. Make the CL1250D-CCPHE part of your Odor Mitigation Plan. Packed with 56 lbs. of activated carbon, the CL1250D-CCPHE eliminates the odor of even the most potent plants while protecting them from mold and mildew growth. Focus on your grow without worry of odor complaints or mold outbreaks.



SKU: CL1250D-CCP

### **Unit Specifications**

Sound Level\* 73 dBA @ 5'

Cabinet Size 25"W x 16.5"T x 59"L

Cabinet Material 16 Ga. Cold Rolled Steel

Cabinet Finish White

48V DC Brushless Axial Flow Fan Motor

Input Power 115V/60Hz/1PH/12A

Hanging Weight 324 lbs. 428 lbs. Shipping Weight 3 Years Warranty

**Options** Silencer\* (Reduces to 63 dBA @ 5')

**Ducting Package** 

Alternative Voltage Options

WiFi/Modbus Smart Controls

7 lb. Carbon After-filter

### **AIRFLOW LEVELS**

CFM	Conditions	W.G.
1500	Max Speed, No Filters	0" w.g.
1420	Max Speed, Clean Filters	1.33" w.g.
900- 1000	Suggested Operating Range for Max Filter Effectiveness	Variable

## Filter Stages

35% Efficient Pleated Pre-Filter, 15" x 25" x 2"

(8) 7lb. Activated Carbon Canisters, 56 lbs. Total

35% Efficient Pleated After-Filter, 15" x 25" x 2"



- ✓ Easy Installation (Pre-Installed Eye Bolts/115V) Wall Plug, 5-15p)
- ✓ Minimal Maintenance (Long Filter Life, Hinged Door) Filter Access, Filter Change Indicator)
- ✓ Adaptable: Can Be Stand-Alone Or Ducted, Flexible Filter Configuration Options
- √ High Static (4" w.g.) Continuously Variable Speed Motor (Maintains Airflow as Filters Load)
- ✓ Industry-Leading Carbon Weight (56 lbs per unit)
- ✓ Combines Clean Room HEPA Filtration + Odor Control

<sup>\*</sup>Noise level measured at typical operating speed