









N E O C I S I O N

GROW LIGHTS



### NEOCISION

## **ELITE 680**

Neocision Elite 680 fixtures feature a 20.6% blue spectra and 45.1% red spectra with a peak at 660nm for your flowering plants. This unique spectra mix creates stronger plants for nutrient uptake with maximized red for increased photosynthesis.

### **FEATURES**

- · Independently tested efficacy of 2.85 µmol/J
- · Industry Leading Horticulture LEDs
- · RJ Port for Plug and Play Control Systems
- · Folding Design for Fast and Easy Installation
- · Leading 660nm LED Count 150 660nm diodes Per Fixture
- · 7 Year Limited Warranty

NEOCISIONGROWLIGHTS.COM

SUPPORT@NEOCISIONGROWLIGHTS.COM



### Technical Data Sheet

# **NEOCISION ELITE 680**

SKU NO: NSE-680

**PRODUCT NAME: ELITE 680** 

### SPECTRUM AND EFFICACY

PPF Efficacy: 2.85 (Tested @ 240 VAC/679 W AC)

 Photon Flux (μmol/s) (400-700nm):
 1937


 Photon Flux Blue (μmol/s) (400-500nm):
 399

 Photon Flux Green (μmol/s) (500-600nm):
 665

 Photon Flux Red (μmol/s) (600-700nm):
 873

 Total Blue/Red - Energy Bands:
 1272

% Blue: 20.63% % Green: 34.33% % Red: 45.04%



### **POWER**

Power Consumption: 680W AC

Power Factor: >0.95
Surge Protection: 6 KV
208V: 3.44 A

**240V:** 2.98 A **277V:** 2.58 A



### **DIMENSIONS**

Fixture Size (driver mounted on the fixture): (L) 43.9" x (W) 43.9" x (H) 3.7"

Fixture Size (without driver): (L) 43.9" x (W) 43.9" x (H) 1.9" Power Supply Dimension: (L) 25.7" X (W) 4.4" X (H) 2.4"

**Driver Net Weight:** 10.1 lbs. **Fixture Net Weight:** 20.4 lbs.



### **OTHER**

Mounting Height: ≥ 12" above canopy

**Light Distribution:** 120°

Input Voltage: 200 - 277 VAC

Manual Dimming Knob: 0-10 V (100% to 10%, then off)

**Built In Control Ports:** RJ 14 input/output **Standard Power Cord (Extensions available):** AWG 18, 6 Foot

Standard Plug: 240 VAC - NEMA 6-15P

Substitute Plugs (Upon request at order): 277 VAC, Pigtails

Adjustable Height Hanging Kit Included: Yes

Fixture and Driver Warranty: 7 Years Limited

ETL Safety Certified\*: Conforms to UL 1598:2021 Ed.5

Certified to CSA C22.2#250.0:2021 Ed.5

\*ETL Safety Certified No. 5020070

**DLC Listed:** Yes



December 2022